

Mixers, vortex, Fisherbrand®



Fisherbrand®

- Speed 0rpm to 3,000rpm
- Touch or continuous operation
- Technopolymer body for higher chemical resistance



Technical Specification

Speed, rpm	0 to 3,000
Orbit diameter, mm	4.5
Dimensions, internal [w x d x h], mm	153 x 170 x 125
Mass, kg	2.7
Power supply	100/240V, 50/60Hz

Catalogue No	Legacy No	Model No	Description
13214789	-	ZX3	Vortex mixer

Accessories

Catalogue No	Legacy No	Description
11707175	-	Micro vial plate
11771174	-	Microtitre plate
11781174	-	Supporting plate

Mixers, vortex, Classic and Wizard, Fisherbrand®

Fisherbrand®

The epoxy painted zinc alloy structure gives excellent resistance to chemical attack. Three anti-sliding feet help to absorb vibration and increase stability. The Wizard vortex mixer has continuous operation and a unique infrared sensing system that detects the presence of the test tube and automatically activates vibration. No pressure is required to activate the motor. The Classic vortex mixer has the traditional touch and continuous operation. Both units come with a standard mixing cup. Other attachments are available.



Technical Specification - General

Speed, rpm	0 to 3,000
Orbit diameter, mm	4.5
Mass, kg	2.4
Dimensions [w x d x h], mm	180 x 220 x 70
Protection	IP42
Electrical supply	230V 50Hz

Catalogue No	Legacy No	Description
11726744	-	ZX Classic vortex mixer
11746744	-	ZX Wizard vortex mixer with infrared sensor

Accessories

Catalogue No	Legacy No	Description
12365107	-	Foam attachment for no. 19 micro vials and 1.5mL Eppendorf® tubes
11792573	-	Foam attachment, customisable
11712583	-	Foam attachment for no. 5 test tubes, 16mm diameter
11792583	-	Foam attachment for microtitre plate
11702593	-	Rubber supporting plate, 50mm diameter
11722583	-	Rubber supporting plate, 94mm diameter (for 11726744 only)
11840992	-	Foam attachment for 4 x test tubes, 29mm diameter