



Continuation

## Pipette filler, RF3000



### Technical Specification

Battery	Lithium ion
Run time, hr	20 (approx.), continuous use
Recharge time, min	60 (approx.)
Nosepiece	5 different colours, autoclavable
For use with	1mL to 100mL glass and plastic pipettes
Filter type	0.45µm replaceable
Electrical supply	100V to 240V supplier with 4 interchangeable plugs
Dimensions (w x d x h), mm	152 x 152 x 41

Catalogue No	Legacy No	Description
12904417	-	RF3000 pipette aid package

### Spare parts

Catalogue No	Legacy No	Description	Pack qty
11304035	-	Replacement filters	5
12914417	-	Replacement power adapter	1
12924417	-	Replacement lithium ion battery	1
11831920	-	Replacement silicon pipette adapter	1
12934417	-	Replacement nose pieces, assorted colours	5



## Pipette filler, Rota-Filler® 5000



- Patented, adjustable pivot arm to change pipetting angle
- LCD display for battery life and speed setting
- Quick recharge and automatic shut off when not in use
- Five speed settings for accurate and sensitive control
- Universal adapter automatically converts to the correct electrical setting

The adjustable pipetting angle allows the most comfortable usage position even in tight and enclosed spaces. The fine speed setting allows single drop accuracy. The rechargeable batteries are quick charge and take approx 1hr for a full charge that will last for 8hr of operation. With a dual bench stand, magnetic wall holder, two replacement 0.45µm filters and a charger.

### Technical Specification

Filter	Hydrophobic, 0.45µm
Range	1mL to 100mL pipettes
Material	Glass and plastic (pipettes) Polypropylene (pipette nozzle, autoclavable)
Battery	1 x NiMH, replaceable

Catalogue No	Legacy No	Description
11384025	-	Rota-Filler® 5000

### Spare part

Catalogue No	Legacy No	Description	Pack qty
11304035	-	Replacement filters	5